

Avanti Plain 301000

Specification according to EN 1307

Identification	Standard	Product data
Type of manufacture	ISO 2424	Tufted 1/10"
Aspect	ISO 2424	Heat-set velour
Pile fibre composition	ISO 2424	100% Pa 6.6. Invista Antron® Brilliance™
Dye method		Continue
Treatment		Teflon
Primary backing	ISO 2424	Woven Polypropylen
Backing	ISO 2424	Textile
Width	CEN/TS 14159	Approx. 400 cm
Pattern report		-
Effective pile thickness	ISO 1766	Approx: 5,00 mm
Total thickness	ISO 1765	Approx: 8,00 mm
Total pile mass	ISO 2424	Approx: 1.000 g/m ²
Total mass	ISO 8543	Approx: 2.400 g/m ²
Number of tufts	ISO 1763	Approx: 225.000 /m ²
Effective pile mass	ISO 8543	-
Stroll test	ISO 6356	≤ 2 kV
Vertical resistance	ISO 10965	-
Horizontal resistance	ISO 10965	-
Classification for use	EN 1307	32 Commercial – normal use
Luxury rating	EN 1307	LC3
Impact sound reduction ΔL_w		Ca. 28 dB (A)
Sound absorption	EN ISO 354	-
Noise reduction	EN ISO 354	-
Thermal conductivity	ISO 8302	Approx: 0,15 m ² K/W
Flammability	EN 13501-1	C _{fl} – s1
ABZ-Nr.		Z-156.601-714



EN 14041:2004
14
0845-CPD-[CX10111](http://www.fletco.com)



Fletco flooring products are to be installed in full accordance with Fletco's installation instructions and recognised trade standards. An effective, regular cleaning and maintenance programme is vital for retaining a high appearance level.

Note: Fletco Floor Products reserve the right to amend this specification without giving prior notice.

For the latest version of the technical specifications, check our internet site: www.fletco.com