

Uno 357000


Specification according to EN 1307

Identification	Standard	Product data
Type of manufacture	ISO 2424	Woven
Aspect	ISO 2424	Loop pile
Pile fibre composition	ISO 2424	100% Pa 6.6. Ascend Ultron®
Dye method		Continue
Treatment		Fletco soil Protection
Primary backing	ISO 2424	PP, PES
Backing	ISO 2424	Textile
Width	CEN/TS 14159	Approx. 400 cm
Pattern report		-
Effective pile thickness	ISO 1766	Approx: 3,00 mm
Total thickness	ISO 1765	Approx: 3,80 mm
Total pile mass	ISO 2424	Approx: 750 g/m ²
Total mass	ISO 8543	Approx: 2.250 g/m ²
Number of tufts	ISO 1763	Approx: 112.000 /m ²
Effective pile mass	ISO 8543	-
Stroll test	ISO 6356	≤ 2 kV
Vertical resistance	ISO 10965	-
Horizontal resistance	ISO 10965	-
Classification for use	EN 1307	33 Commercial – heavy use
Luxury rating	EN 1307	LC1
Impact sound reduction ΔL_w		Approx. 16 dB (A)
Sound absorption	EN ISO 354	-
Noise reduction	EN ISO 354	-
Thermal conductivity	ISO 8302	Approx: 0,06 m ² K/W
Flammability	EN 13501-1	C _{fl} – s1

ABZ-Nr.



EN 14041:2004
14
2531-CPR-[CXA10114](#)



Fletco flooring products are to be installed in full accordance with Fletco's installation instructions and recognised trade standards. An effective, regular cleaning and maintenance programme is vital for retaining a high appearance level.

Note: Fletco Floor Products reserve the right to amend this specification without giving prior notice. For the latest version of the technical specifications, check our internet site: www.fletco.com