





Fletco textile floor coverings

Zenith 371000

Specification according to EN 1307

Identification	Standard	Data
Type of manufacture	ISO 2424	Tufting 1/10"
Aspect	ISO 2424	Cut pile
Pile fibre composition	ISO 2424	100% PA 6.6. Invista Antron® Brilliance™
Dye method		Continue
Treatment		Teflon
Primary backing	ISO 2424	Polyester non woven
Backing	ISO 2424	Textil
Width	CEN/TS 14159	400 cm
Pattern report		-
Effective pile thickness	ISO 1766	Approx. 3,50 mm
Total thickness	ISO 1765	Approx. 6,50 mm
Total pile mass	ISO 2424	Approx. 1.000 g/m ²
Total mass	ISO 8543	Approx. 2.400 g/m ²
Number of tufts	ISO 1763	Approx. 220.000 /m ²
Effective pile mass	ISO 8543	-
Stroll test	ISO 6356	≤2 kV
Vertical resistance	ISO 10965	-
Horizontal resistance	ISO 10965	-
Classification for use	EN 1307	33 Commercial – heavy use
Luxury rating	EN 1307	LC3
Impact sound reduction ΔL_w		Approx. 26 dB(A)
Sound absorption	EN ISO 354	-
Noise reduction	EN ISO 354	-
Thermal conductivity	ISO 8302	Approx. 0,14 m ² K/W
Flammability	EN 13501-1	C _{fl} – s1
ABZ-Nr.		Z-156.601-714



Fletco flooring products are to be installed in full accordance with our installation instructions and recognised trade standards. An effective, regular cleaning and maintenance programme is vital for retaining a high appearance level. Note: Fletco floor products reserve the right to amend this specification without giving prior notice. For the latest version of the technical specifications, check our internet site: www.fletco.com