



Fletco textile floor coverings

Nordic 394000

Specification according to EN 1307

Identification	Standard	Product data
Type of manufacture	ISO 2424	Woven
Aspect	ISO 2424	Loop pile
Pile fibre composition	ISO 2424	100% PA 6.6. Ascend Ultron®
Dye method		Continue
Treatment		Fletco soil Protection
Primary backing	ISO 2424	PES
Backing	ISO 2424	Textile
Width	CEN/TS 14159	Approx. 400 cm
Pattern report		-
Effective pile thickness	ISO 1766	Approx: 2,00 mm
Total thickness	ISO 1765	Approx: 3,50 mm
Total pile mass	ISO 2424	Approx: 550 g/m ²
Total mass	ISO 8543	Approx: 1.900 g/m ²
Number of tufts	ISO 1763	Approx: 156.000 /m ²
Effective pile mass	ISO 8543	-
Stroll test	ISO 6356	≤ 2 kV
Vertical resistance	ISO 10965	-
Horizontal resistance	ISO 10965	-
Classification for use	EN 1307	33 Commercial – heavy use
Luxury rating	EN 1307	LC1
Impact sound reduction ΔL_w		Approx: 16 dB (A)
Sound absorption	EN ISO 354	-
Noise reduction	EN ISO 354	-
Thermal conductivity	ISO 8302	Approx: 0,06 m ² K/W
Flammability	EN 13501-1	C _{fl} – s1
ABZ-Nr.		



Fletco flooring products are to be installed in full accordance with Fletco's installation instructions and recognised trade standards. An effective, regular cleaning and maintenance programme is vital for retaining a high appearance level.
 Note: Fletco Floor Products reserve the right to amend this specification without giving prior notice.
 For the latest version of the technical specifications, check our internet site: www.fletco.com